



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7: B22C 9/24, B22D 27/04, 19/00

A1

(11) International Publication Number:

WO 00/45978

(43) International Publication Date:

10 August 2000 (10.08.00)

(21) International Application Number:

PCT/FI00/00054

(22) International Filing Date:

27 January 2000 (27.01.00)

(30) Priority Data:

990198

3 February 1999 (03.02.99)

Published

(71) Applicant (for all designated States except US): OUT-OKUMPU OYJ [FI/FI]; Riihitontuntie 7, FIN-02200 Espoo

(FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): LEPPÄNEN, Yrjö [FI/FI]; Mikonkatu 30 A 25, FIN-28100 Pori (FI). MÄKINEN, Pertti [FI/FI]; Suulotintie 35, FIN-28610 Pori (FI). SALMI-NEN, Matti [FI/FI]; Ahjonkatu 9, FIN-20250 Nakkila (FI).

(74) Agent: OUTOKUMPU OYJ; Patent Services, P.O. Box 27, FIN-02201 Espoo (FI).

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of


ZA, Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI,

(81) Designated States: AU, BG, BR, CA, CN, DE, ES, ID, IN, JP, KR, KZ, MX, NO, PL, PT, RO, RU, SE, TR, US, YU,

FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

amendments.

(54) Title: CASTING MOULD FOR MANUFACTURING A COOLING ELEMENT AND COOLING ELEMENT MADE IN SAID MOULD



(57) Abstract

The invention relates to a casting mould for manufacturing of a cooling element for a pyrometallurgical reactor, wherein the casting mould is at least partly cooled and lined with a material that can withstand high temperatures. The invention also relates to the cooling element made in the mould, inside which cooling pipes made of nickel copper are placed during fabrication.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
ΑT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Моласо	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ircland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	İtaly	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	
СН	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Yugoslavia Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand	ZW	Zimoabwe
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG			
			Diocita	30	Singapore		

WO 00/45978

5


10

15

20

25

30



09/889942 PCT/F100/00054 JC17 Rec a PCT/PTO 25 JUL 2001

CASTING MOULD FOR MANUFACTURING A COOLING ELEMENT AND COOLING ELEMENT MADE IN SAID MOULD

The invention relates to a casting mould for the manufacturing of a cooling element for a pyrometallurgical reactor, wherein the casting mould is at least partly cooled and lined with a material that can withstand high temperatures. The invention also relates to the cooling element made in the said mould.

In pyrometallurgical processes, the brickwork of a reactor is protected by water-cooled cooling elements so that, due to the cooling effect, the heat coming to the surface of the brickwork is transferred via the cooling element to water, wherein the wear on the lining decreases considerably in comparison with a reactor not provided with cooling. The decrease in wear is caused by the result of cooling, a so-called autogenic lining, formed of slag and other molten phases that attaches to the fireproof surface of the lining.

Traditionally, cooling elements are manufactured by two methods: Firstly, the elements can be fabricated by sand casting. In this method, cooling pipes made of highly thermo-conductive material such as copper are set in a mould dug in the sand, so that during casting, there is cooling either by air or water occurring around the pipes. The element to be cast around the piping is also made of a highly thermo-conductive material, advantageously copper. This fabrication method has been described in for example GB patent 1386645. The problem with this method is the uneven attachment of the piping that acts as flow channel to the surrounding casting material, since part of the piping may be totally detached from the element cast around it and part of the piping may be completely melted and therefore damaged. If no metallic bond is formed between the cooling pipe and the other element cast around it, heat transfer will not be efficient. If the piping melts completely, it will prevent the flow of cooling water. The casting properties of the casting material can be enhanced by, for example, mixing some phosphorus into the copper, which will improve the metallic bond forming



between the piping and casting material, but in this way the heat transfer properties (thermal conductivity) of the cast copper deteriorate considerably with just small additions. Advantages of this method can be listed as the comparatively low fabrication costs and independence from dimensions.

5

20

25

30

A fabrication method has also been used, where glass piping in the shape of a flow channel is set into the cooling element mould which glass piping is broken after casting, so that a flow channel forms inside the element.

US patent 4382585 describes another, widely used fabrication method for cooling elements, according to which the element is fabricated for example from rolled copper plate, by machining the necessary channels. The advantage of this method is the dense, strong structure and good heat transfer from a cooling medium such as water to the element. The drawbacks are dimensional limitations (size) and the high cost.

Now a casting mould has been developed for manufacturing a cooling element for a pyrometallurgical reactor to replace the previous sand casting. The casting mould is constructed from separate, highly thermo-conductive copper plates, of which at least some are water-cooled. Since the cooling element itself is in most cases copper, the construction plates of the casting mould should be isolated from the cast copper, and this occurs by lining the inner part of the mould with highly thermo-conductive material such as graphite plate, so that the parts of the mould attach themselves to the surface by means of underpressure. Graphite prevents the melt poured into the mould from sticking to the surface of the mould. The cooling element casting mould is advantageously provided with a cope, so the casting can be done in shielding gas. Prior to casting, the cooling pipes necessary for cooling water circulation that are going to go inside the cooling element are placed into the mould. This piping is preferably made of nickel copper pipe, because the melting point of Ni-Cu pipe is higher than the copper being cast around it and therefore there is no risk of the pipe melting during casting.

The essential features of the invention will become apparent in the attached patent claims.

The casting mould construction described in this invention offers the following advantages:

- Thanks to the cooled mould and graphite lining, a tight and fine-grained casting is formed, particularly at the base of the casting mould.
- The construction of the mould means that the cooling element forms a smooth surface, which is not vulnerable to corroding smelting conditions.

The nickel copper used as the material for the cooling element cooling pipes facilitates a good welding of the piping to the actual element.

The construction of the casting mould can be developed further so that it can also be used for manufacturing cooling elements designed for special purposes. This occurs for example by adding graphite or fireproof shaped pieces to the mould, so that the finished element design differs correspondingly from the plated version.

20

30

The invention can be described further with the aid of the attached diagrams, where Figure 1 presents a principle drawing of the casting mould according to this invention and

Figure 2 shows the casting mould in cross-section, with which special-purpose cooling elements can be cast.

Figure 1 shows a principle drawing of a cooling element casting mould 1. The mould is composed of a mould base plate 2, which is furnished with cooling pipes 3. The mould also has side walls 4 and 5 and end walls from which only a back wall 6 is shown in the drawing. In the drawing, only the base plate is furnished with cooling pipes but, if required, the side and end walls can also be equipped for cooling. The front end wall has been left out



of the drawing for reasons of clarity, although it definitely belongs to the mould.

The inside of the mould is lined with graphite plates 7. The cooling element cooling pipes 8, which are advantageously made of nickel copper, are supported inside the mould. The mould is also equipped with a cope (not shown) so that shielding gas can be used to prevent oxidation of the element to be cast.

In Figure 2 it can be seen that shaped pieces 9 can be placed on the base of the mould, which are made of graphite or some other fireproof material. By means of these shaped pieces, the side 11, which will come into contact with mould base 2 of cooling element 10, can be shaped as desired.


5

15


PATENT CLAIMS

- 1. A casting mould formed of base (2), wall (4,5) and end plates (6) for manufacturing of a pyrometallurgical reactor cooling element, characterized in that the casting mould (1) made of copper plates is at least partly equipped with cooling pipes (3) and that the mould is lined on the inside with a plate (7) resistant to high temperatures.
- 2. A casting mould according to claim 1, characterized in that the casting
 mould (1) is lined with graphite plates (7).
 - 3. A casting mould according to claim 1, **characterized in that** the plates (7) resistant to high temperatures are fixed to the surface of the mould (1) by means of underpressure.
 - 4. A casting mould according to claim 1 characterized in that shaped pieces (9) made of graphite or fire-resistant material are placed on the base of the casting mould (1).
- 5. A pyrometallurgical reactor cooling element fabricated in a mould, characterized in that cooling pipes (8), placed inside cooling element (10) are manufactured of nickel copper.
- 6. A cooling element according to claim 4, **characterized in that** during manufacturing of the cooling element (10), one side of the element (11) is formed by means of shaped pieces (9) placed on the base of the casting mould.

1 / 2



2/2





International application No.

PCT/FI 00/00054

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B22C 9/24, B22D 27/04, B22D 19/00
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B22C, B22D, F27D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE, DK, FI, NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	GB 1386645 B (OUTOKUMPU OY), 12 March 1975 (12.03.75), page 4, line 20 - line 27, claim 1	1-4
		1
Y	US 4252178 A (ANTHONY W. HUDD), 24 February 1981 (24.02.81), column 3, line 17 - line 32, figure 1	1-4
A	GB 1547761 B (DAVY-LOEWY LIMITED), 27 June 1979 (27.06.79), claims 1,4	1-4
Α .	EP 0816515 A1 (MAN GUTEHOFFNUNGSHÜTTE AKTIENGESELLSCHAFT), 7 January 1998 (07.01.98), column 2, line 27 - line 36	1-6

X	Further	documents	are listed	in the	continuation	of Box C.	

See patent family annex.

- Special categories of cited documents:
- document defining the general state of the art which is not considered to be of particular relevance
- "E" erlier document but published on or after the international filing date
- document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- document referring to an oral disclosure, use, exhibition or other means
- document published prior to the international filing date but later than the priority date claimed
- later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

06 -07- 2000

<u>28 June 2000</u>

Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Mårten Hulthén/MP


Telephone No. + 46 8 782 25 00

Form PCT/ISA/210 (second sheet) (July 1992)

International application No. PCT/FI 00/00054

	107/11 00/	
C (Continu	ation). DOCUMENTS CONSIDERED TO BE RELEVANT	
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
A	WO 8700779 A1 (FONDERIES ET AFFINAGE DE L'ISERE), 12 February 1987 (12.02.87), abstract	1-4
A	WO 9830345 A1 (PAUL WURTH S.A.), to July 1998 (16.07.98), abstract	1-4
A	GB 2007549 A (HITACHI LTD), 23 May 1979 (23.05.79), figures 2-3	1-4
х	GB 1424532 B (JAMES BROWN & SONS LIMITED), 11 February 1976 (11.02.76), page 1, line 58 - line 62; page 2, line 28 - line 36, figures 1-5, claims 1,6,7	5
Y		6
Υ	US 4892293 A (YOICHIRO KATO ET AL), 9 January 1990 (09.01.90)	6
A	GB 2261394 A (THYSSEN GUSS AG), 19 May 1993 (19.05.93), page 2, line 7 - line 16	5-6
A	US 4620507 A (HIROMICHI SAITO ET AL), 4 November 1986 (04.11.86), column 4, line 18 - line 22, figures 1-2	5-6
	A/210 (continuation of second sheet) (July 1992)	





Box 1	Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)
This inte	ernational search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:
1.	Claims Nos.: because they relate to subject matter not required to be searched by this Authority, namely:
2.	Claims Nos.: because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3.	Claims Nos.: because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).:
Box II	Observations where unity of invention is lacking (Continuation of item 2 of first sheet)
I. C	national Searching Authority found multiple inventions in this international application, as follows: laims 1-4 relate to a casting mould made of copper plates. laims 5-6 relate to a cooling element involving cooling pipes anufactured of nickel copper.
2.	As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims. As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee. As only some of the required additional search fees were timely paid by the applicant, this international search report overs only those claims for which fees were paid, specifically claims Nos.:
. N	to required additional search fees were timely paid by the applicant. Consequently, this international search report is estricted to the invention first mentioned in the claims; it is covered by claims Nos.:
lemark on	Protest The additional search fees were accompanied by the applicant's protest. No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT Information on patent family members

International application No. 02/12/99 | PCT/FI 00/00054

					02/12/33	1 01/11	00/00054	
	Patent docum	eport	Publication date		Patent family member(s)		Publication date	
GE	3 138664	15 B	12/03/75	FI	47052	В	31/05/73	
US	425217	78 A	24/02/81	AL	519742	В	17/12/81	
				AU			15/11/79	
				BE				
				BR		Â	17/11/78	
				DD	135863	<u>^</u>	26/12/78	
				DE	2821999	A C	06/06/79	
				DE		A,C	07/12/78	
							18/12/86	
				DK			20/11/78	
				ES			16/01/79	
				FI	62776		30/11/82	
				FI	781595		20/11/78	
				FR	2391012	A,B	15/12/78	
				GB	1583592	A	28/01/81	
				IE	47272		08/02/84	
				ĪĪ	1094767		02/08/85	
				ĪŤ	7823610		· •	
				ĴP	1377370		00/00/00	
				JP			08/05/87	
				JP			08/01/79	
					61043136		26/09/86	
				LU	79672		13/06/79	
				NL	7805379		21/11/78	
				SE	435909 E	3,C	29/10/84	
				SE	7805718 A		20/11/78	
				YU	40520 E		28/02/86	
				YU	120478 A	\ 	30/04/84	
GB	1547761	В	27/06/79	AU	503590 B	3	13/09/79	
				AU	1277376 A	1	13/10/77	
				DE	2615228 A		28/10/76	
				FR	2306767 A	B	05/11/76	
				ZA	7602086 A	, -	27/04/77	
EP	0816515	A1	07/01/98	CA	2209682 A		05/01/98	
			•	DE	29611704 U			i
				US	5904893 A		17/10/96	
					A CEOFFEE		18/05/99	
WO	8700779	A1	12/02/87	EP	0231311 A		12/00/07	
			, -2, 0,	FR	2585598 A		12/08/87	
					43033398 A	,¤ 	06/02/87	İ
MO	9830345	A1	16/07/98	AU	6207198 A		03/08/98	
				EP	0951371 A		27/10/99	1
				LU	90003 A		09/07/98	}
				LU	90146 A		30/03/99	
				ZA	9800076 A		08/07/98]
GB	2007549	Α	23/05/79	DE	2844520 A,	 В С	26 /04 /70	
				JP	1115560 C	-	26/04/79	- 1
					54059661 A		29/09/82	
					57001757 B		14/05/79 12/01/82	ļ

INTERNATIONAL SEARCH REPORT Information on patent family members

02/12/99

International application No.

PCT/FI 00/00054

cite	Patent documen ed in search rep	t ort	Publication date		Patent family member(s)	Publication date
GB	1424532		11/02/76	AR AU AU BE CA CH DD DE ES FR IT JP LU NL SE US	197029 A 467449 B	08/03/74 04/12/75 19/09/74 16/07/73 25/05/76 30/06/76 05/02/74 04/10/73 16/01/76 02/11/73 10/01/76 10/10/74 19/01/74 22/05/73 24/09/73 09/02/76 10/12/74
US	4892293	Α	09/01/90	ZA CA DE IT IT JP JP JP KR	7301865 A 1303850 A 3910136 A,C 1228771 B 8919948 D 1801558 C 2163307 A 5007444 B 9608722 B	19/12/73
GB	2261394	A	19/05/93	DE FR	4134066 A 2682312 A	22/04/93 16/04/93
US	4620507	A	04/11/86	AU AU BR CA EP SE JP JP LU MX	548885 B 8108082 A 8201170 A 1171651 A 0059960 A,B 0059960 T3 1027821 B 1547621 C 57146463 A 83985 A 157808 A	09/01/86 09/09/82 18/01/83 31/07/84 15/09/82 31/05/89 09/03/90 09/09/82 08/07/82 15/12/88